



Paint and Paper Arch Clock

By Janet Wilhelm for Walnut Hollow®

Materials:

- [Walnut Hollow® #27640 Arch Clock with Bezel](#)
- Making Memories Shapes
- Making Memories Brads
- (2) Sheets of Coordinating Decorative Paper & 2"x2" piece of White Paper
- Paint (color that coordinates with paper)
- Other supplies: AA battery, adhesive spray or decoupage medium, brush, craft glue, double sided adhesive dots, paper towel, ruler, sandpaper, scissors, spray varnish, wire cutter, X-ACTO knife

Instructions:

1. To prepare wood for painting, remove bezel and use sandpaper to lightly sand wood surface. Remove dust with paper towel.
2. Use brush to apply paint to wood surface. Let dry and apply second coat if needed. Let dry.
3. Apply 2-3 coats of spray varnish for a protective finish.
4. Use ruler to measure width and height of clock front. Use pencil and ruler to draw pattern. Use scissors to cut paper to fit front of clock. Do the same for bottom ledge of clock using coordinating paper. Use adhesive spray or decoupage medium to adhere paper to clock front and ledge. Use scissors or X-ACTO knife to remove paper from bezel opening. Use scissors to trim any excess paper around clock front.
5. Replace bezel. Use wire cutter to remove back of brads. Use adhesive dots to adhere brads around bezel.
6. Refer to photo for suggestions. Adhere decorative paper to Shapes. Trim with scissors. Use craft glue to adhere white paper onto back of opening. Use craft glue to adhere a Shape over white paper.
7. Insert AA battery.

